WALL & CEILING

NON-WOVEN DESIGN2WALL LATEX 200

matt 2501, 200 g/m^2

Pre-coated non-woven wallpaper with smooth finish

The Non-woven design2wall Latex 200 matt is a pre-coated non-woven wallpaper for inkjet printing with latex and UV inks. It produces impressive wall decoration and wallpapers due to its matt, homogeneous surface. This product can be pasted without further surface protection, with standard non-woven wallpaper paste. It is flame retardant and certified.

Technologies

LAT UV

Properties

Advantages

- High opacity for good coverage of the underlying surface
- Good lightfastness
- High wet and dry strength
- Dry strippable
- PVC free
- FSC® certified
- Flame retardant and C-s1, d0 certified according to European Standard EN 13501-1
- Hang using standard non-woven wallpaper paste

OEKO-TEX® STANDARD 100 D13-0796 HOHENSTEIN HTTI

FSC www.fsc.org FSC® C005732 The mark of responsible forestry

General tips

To maintain the high quality of this wallpaper, it should be stored and converted in a climate of 30 – 65 % relative humidity and at a temperature of 10 – 30°C (50 – 86°F).

Physical data

Name	Value	Norm
Weight [g/m²]	200	ISO 536
Thickness (paper) [µm]	234	ISO 534
ISO Brightness [%]	90	ISO 2470-1
Opacity [%]	95	ISO 2471
Tensile strength MD [N/15mm]	165	ISO 1924-3/2/300
Tensile strength CD [N/15mm]	107	ISO 1924-3/2/300
Wet tensile strength MD [N/15mm]	63	ISO 3781
Wet elongation CD (Fenchel) [%]	0.2	A 10-011/27

The values stated above are only for orientation. Before using our print media please check its compatibility for your printer and the intended application. We cannot be held responsible for any mistakes resulting from technical changes in the printing process and with printing components. Product design changes to our products technical developments may be carried out without prior notice.